

## **Downdraft Table**

These overhead units can be strategically placed to eliminate dust from the workplace, where capturing at the source may not be possible. The cartridge filters, which filter dust and smoke particles too small for most overhead units, can be cleaned over and over again. With the inlet shroud able to be rotated 360 degrees, the user can direct the suction where it is needed most.

**Call today to discuss your application!**

### **Standard Features:**

- Totally enclosed fan cooled (TEFC) motor
- Capacity: 3000 ICFM
- One year warranty on parts and labor (except filters)
- Sound level: 72 dB (A)
- Filtration: cartridge filters @ 0.05 micron
- Motor: 1 ½ Hp, 1 or 3 Ph
- Voltages 220 1 Ph; or 230/460 & 575 3 Ph
- Dimensions: 26" W x 26" H x 74" L
- Weight: 220 lbs
- All metal construction
- Magnehelic gauge

### **Options:**

- Carbon filtration
- HEPA filtration
- Cable lift system (includes pulleys, cables, and winch)
- Mobile unit carrier
- Rubber mat



**AIR DYNAMICS INDUSTRIAL SYSTEMS CORPORATION**

300 North Queen Street, York, PA 17403 USA

Email: [sales@airdynamics.net](mailto:sales@airdynamics.net)

TEL: 717-854-4050

FAX: 717-854-4020

• Pollution Control Systems • Industrial Vacuum Systems • Oil Mist Collection Systems

Check out our full feature website at [www.airdynamics.net](http://www.airdynamics.net)