



## **Downdraft Table**

These models are designed and built specifically to deal with metal cutting, grinding, and sanding and contain two flame retardant pans built over the filters to protect them from exposure to hot sparks. This also extends the life of the filters. The filters are cleaned automatically by compressed air. This cleaning procedure can also be done manually at any time.

**Call today to discuss your application!**

### **Standard Features:**

- Totally enclosed fan cooled (TEFC) motor
- Capacity: 4000 ICFM
- Push button and automatic cleaning
- One year warranty on parts and labor (except filters)
- Sound level: 80 dB (A)
- Filtration: 100% spunbound polyester - flame retardant  
99.9% efficient @ .5 micron
- Motor: 5 HP 1PH or 3PH
- Weight: 1200 lbs
- Voltages: 220 – 1PH or 230 – 460 – 575 – 3PH
- Dimensions: 48" W x 72" L x 36" H
- Grate covered with very durable sprayed-on urethane
- All metal construction
- Water pan
- 3 sided 20" tall spark shield
- Exhaust muffler

### **Options:**

- Hydraulic motors to run fans
- Explosive proof motor
- Exhaust chimney
- Non-motorized unit for central systems
- Other filter medias available
- Castors
- Fiberglass grate
- Rubber mat

**AIR DYNAMICS INDUSTRIAL SYSTEMS CORPORATION**

300 North Queen Street, York, PA 17403 USA  
Email: [sales@airdynamics.net](mailto:sales@airdynamics.net)

TEL: 717-854-4050

FAX: 717-854-4020

• Pollution Control Systems • Industrial Vacuum Systems • Oil Mist Collection Systems

Check out our full feature website at [www.airdynamics.net](http://www.airdynamics.net)