



Downdraft Table for Metal Cutting, Grinding, and Sanding

These models are designed and built specifically to deal with metal cutting, grinding, and sanding and contain four flame retardant pans built over the filters to protect them from exposure to hot sparks. This also extends the life of the filters. The filters are cleaned automatically by compressed air. This cleaning procedure can also be done manually at any time.

Call today to discuss your application!

Standard Features:

- Totally enclosed fan cooled (TEFC) motor
- Capacity: 4000 ICFM
- Push-button and automatic cleaning
- One year warranty on parts and labor (except filters)
- Filtration: 100% spunbound polyester - flame retardant
99.9% efficient @ .5 micron
- Motor: 5 HP
- Weight: 1400 lbs
- Voltages: 220- 1PH or 230-460-575-3PH
- Dimensions: 48" W x 96" L x 36" H
- Grate covered with very durable sprayed-on urethane
- All metal construction
- Water pan
- Exhaust muffler

Options:

- Hydraulic motors to run fans
- Explosive proof motor
- Exhaust chimney
- Non-motorized unit for central systems
- Other filter medias available
- 3-Sided 20" spark shield
- Fiberglass grate
- Rubber mat
- Castors

AIR DYNAMICS INDUSTRIAL SYSTEMS CORPORATION

300 North Queen Street, York, PA 17403 USA

Email: sales@airdynamics.net

TEL: 717-854-4050

FAX: 717-854-4020

• Pollution Control Systems • Industrial Vacuum Systems • Oil Mist Collection Systems

Check out our full feature website at www.airdynamics.net